

Quantité	Description												
1	ALPHA1 L 25-40 180  Note ! La photo produit peut différer du produit réel Référence: 99160579 Grundfos ALPHA1 L 25-40 180 is a high-efficiency circulator pump with permanent-magnet motor (ECM technology). The pump features three control modes; radiator heating mode, underfloor heating mode and constant curve/constant speed. Furthermore, the speed can be controlled by a low-voltage PWM (Pulse Width Modulation) signal. The pump has a ceramic shaft and radial bearings, carbon thrust bearing, stainless-steel rotor can, bearing plate and rotor cladding, composite impeller, all of which contribute to long life, and the pump is self-venting, which contributes to easy commissioning as well as simple selection of control mode. The compact design featuring pump head with integrated control box and control panel fits into most common installations as well as boilers. The pump and motor form an integral unit without shaft seal. The pump is of the wet-runner design. This means the bearings are lubricated by the pumped liquid. These constructions ensure maintenance-free operation. The pump housing is made of cast iron and is electrocoated to improve the corrosion resistance. The motor is a synchronous permanent-magnet rotor/compact-stator motor. The pump controller is incorporated in the control box, which is fitted to the stator housing and connected to the stator via a terminal plug. Features ALPHA1 L • Three constant curves/constant speed. • Radiator heating mode. • Underfloor heating mode. • PWM profile for heating applications (profile A). The PWM signal is a method for generating an analog signal using a digital source. • Energy-optimised, complies with the ErP directive • Unblocking screw, accessible from the front of the control box. • Runs reliably and efficiently under even the most demanding conditions • Adjustable and flexible installer plug, with two possible cable gland positions. Liquide: <table> <tr> <td>Liquide pompé:</td><td>Eau</td></tr> <tr> <td>Plage température liquide:</td><td>2 .. 95 °C</td></tr> <tr> <td>Selected liquid temperature:</td><td>60 °C</td></tr> <tr> <td>Masse volumique:</td><td>983.2 kg/m³</td></tr> </table> Technique: <table> <tr> <td>Classe TF:</td><td>95</td></tr> <tr> <td>Certifications sur la plaque signalétique:</td><td>CE,VDE,EAC</td></tr> </table>	Liquide pompé:	Eau	Plage température liquide:	2 .. 95 °C	Selected liquid temperature:	60 °C	Masse volumique:	983.2 kg/m³	Classe TF:	95	Certifications sur la plaque signalétique:	CE,VDE,EAC
Liquide pompé:	Eau												
Plage température liquide:	2 .. 95 °C												
Selected liquid temperature:	60 °C												
Masse volumique:	983.2 kg/m³												
Classe TF:	95												
Certifications sur la plaque signalétique:	CE,VDE,EAC												

Quantité	Description
	Matériaux: Corps de pompe: Fonte EN 1561 EN-GJL-150 ASTM A48-150B Roue mobile: Composite/PES 30 % GF Installation: Plage température ambiante: 0 .. 55 °C Pression maximale de service: 10 bar Raccordement tuyauterie: G 1 1/2 Pression par étage: PN 10 Entraxe: 180 mm Donnée électrique: Puissance élec.-P1: 4 .. 25 W Fréquence d'alimentation: 50 / 60 Hz Tension nominale: 1 x 230 V Intensité maximum consommée: 0.05 .. 0.26 A Indice de protection (IEC 34-5): X4D Classe d'isolement (IEC 85): F Autres: Energie (EEI): 0.20 Poids net: 2.1 kg Poids brut: 2.2 kg Colisage: 0.004 m3 Country of origin: DK Code douanier: 84137030

Description	Valeur
Information générale:	
Nom produit:	ALPHA1 L 25-40 180
Code article:	99160579
Numéro EAN::	5712607862633
	5712607862633
Prix:	252.00 EUR
Technique:	
Pression maxi:	40 dm
Classe TF:	95
Certifications sur la plaque signalétique:	CE,VDE,EAC
Modèle:	C
Matériaux:	
Corps de pompe:	Fonte
	EN 1561 EN-GJL-150
	ASTM A48-150B
Roue mobile:	Composite/PES 30 % GF
Installation:	
Plage température ambiante:	0 .. 55 °C
Pression maximale de service:	10 bar
Raccordement tuyauterie:	G 1 1/2
Pression par étage:	PN 10
Entraxe:	180 mm
Liquide:	
Liquide pompé:	Eau
Plage température liquide:	2 .. 95 °C
Selected liquid temperature:	60 °C
Masse volumique:	983.2 kg/m³
Donnée électrique:	
Puissance élec.-P1:	4 .. 25 W
Fréquence d'alimentation:	50 / 60 Hz
Tension nominale:	1 x 230 V
Intensité maximum consommée:	0.05 .. 0.26 A
Indice de protection (IEC 34-5):	X4D
Classe d'isolement (IEC 85):	F
Protection moteur:	AUCUN
Protection thermique:	ELEC
Commandes:	
Réf boîte à bornes:	6H
Autres:	
Energie (EEI):	0.20
Poids net:	2.1 kg
Poids brut:	2.2 kg
Colisage:	0.004 m3
Country of origin:	DK
Code douanier:	84137030

